## **ELEVATION CERTIFICATE**

O.M.B. No 3067-0077 Expires May 31, 1993

## FEDERAL EMERGENCY MANAGEMENT AGENCY

NATIONAL FLOOD INSURANCE PROGRAM 'NTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to e elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to nine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages. SECTION A PROPERTY INFORMATION FOR INSURANCE COMPANY USE BUILDING OWNER'S NAME POLICY NUMBER ROBERT A.C. CICCO JR. STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg, Number) OR P.O. ROUTE AND BOX NUMBER COMPANY NAIC NUMBER 2740 GULF BOULEVARD UNIT 1 OTHER DESCRIPTION (Lot and Block Numbers, etc.) LOT 1, HOLIDAY VILLAS OF BELLEAIR BELLEAIR BEACH FLORIDA ZIP CODE 34640 SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 1. COMMUNITY NUMBER 2. PANEL NUMBER 4. DATE OF FIRM INDEX 6. BASE FLOOD ELEVATION (in AO Zones, use depth) 5. FIRM ZONE 125089 0002 В 3-2-83 A-11 11' 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: \_\_\_\_\_ feet NGVD (or other FIRM datum-see Section B, Item 7) SECTION C BUILDING ELEVATION INFORMATION ring the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best ribes the subject building's reference level 5 RM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of \_\_\_\_\_16\_..4 feet NGVD (or other FIRM datum-see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of \_\_\_\_\_ feet NGVD (or other FIRM datum-see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is \_\_\_\_\_. feet above \_\_\_ or below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is ...... feet above ..... or below ..... (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? 

Yes 

No 

Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: 🗌 NGVD '29 🔲 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: U Yes 以XNo (See Instructions on Page 4) 5. The reference level elevation is based on: 💢 actual construction 🔲 construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is: 17 feet NGVD (or other FIRM datum-see Section B, Item 7). SECTION D COMMUNITY INFORMATION community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest as defined by the ordinance is: \_\_\_\_\_\_. feet NGVD (or other FIRM datum-see Section B, Item 7).

2. Date of the start of construction or substantial improvement \_\_\_\_

## SECTION E CERTIFICATION


a Constant and a setting for the Constant

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME			L	ICENSE NUMBER (or Affix Seal)		
	LAUREN R. I	PENNY			4931	\$25 H 65
TITLE	2		COMPANY NAME			
	PRESIDENT	L.	R. PENNY AND	ASSOCIATES, INC.		
ADDRESS	11922 SEMINOLE	BOULEVARD	LARGO		FLORIDA STATE	34648
SIGNATURE	Lauren R.	Penny		DATE 1-12-92	PHONE 813	-398-4360
Copies sho	ould be made of this C	ertificate for: 1) c	community official,	2) insurance agent/comp	pany, and 3) buildin	g owner.
COMMENT	rs:NOTE:	BENCH MARK U	ISED HALL E EL	EV. 5.48 LOCATED S	S.E. CORNER	19
	INTERSECTION	N OF GULF BO	ULEVARD AND 2	IST. STREET	•	
		AS COUNTY				
				2		



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.